

64673 300 W 240 V

Halogen studio lamps, single-ended



Areas of application

- Professional film and TV work
- Theater and concert stages
- Entertainment

Product features

- Operation at mains voltage: 120 V | 230 V | 240 V
- Color temperature: 3,000 K (with longer lifespan)
- Color temperature: 3,200 K (for professional film and TV work)





Technical data


Electrical data

| Nominal wattage | 300.00 W |
|-----------------|----------|
| Nominal voltage | 240 V |

Photometrical data

| Nominal luminous flux | 6800 lm |
|-----------------------|---------|
| Color temperature | 3100 K |

Dimensions & weight







| Diameter | 18.0 mm | |
|---------------------------|------------|--|
| Length | 90.0 mm | |
| Light center length (LCL) | 46.5 mm | |
| Illuminated field | 6.5*13 mm² | |
| Filament diameter | 13.0 mm | |

Lifespan

| Lifespan | 200 h |
|----------|-------|
| | |

Additional product data

| Base (standard designation) | GY9.5 |
|-----------------------------|-------|
|-----------------------------|-------|

Capabilities

| Burning position Any |
|----------------------|
|----------------------|

Certificates & standards

| EEI – Energy Label | В |
|--------------------|---|
|--------------------|---|

Country specific categorizations

| ANSI code | FSK |
|-----------------|-------|
| LIF | CP/81 |
| Order reference | 64673 |

Country specific information

| Product code | METEL code | SEG-No. | STK-Number | UK Org |
|---------------|--------------|---------|------------|--------|
| 4008321099808 | OSRH64673240 | - | - | - |

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.



Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4008321099808 | 64673 300 W 240 V | Folding carton box 1 | 111 mm x 42 mm x 48 mm | 0.22 dm ³ | 27.00 g |
| 4008321099815 | 64673 300 W 240 V | Shipping carton box 12 | 180 mm x 127 mm x 140 mm | 3.20 dm ³ | 363.00 g |
| 4008321131263 | 64673 300 W 240 V | Folding carton box 1 | - x - x - | | |
| 4008321131270 | 64673 300 W 240 V | Shipping carton box 12 | 180 mm x 140 mm x 127 mm | 3.20 dm ³ | 365.00 g |
| 4052899015487 | 64673 300 W 240 V | Folding carton box 1 | 42 mm x 42 mm x 111 mm | 0.20 dm³ | 33.80 g |
| 4052899015494 | 64673 300 W 240 V | Shipping carton box 12 | 180 mm x 140 mm x 127 mm | 3.20 dm ³ | 493.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

A summary of studio lamps can be found on the halogen studio lamps poster.

For more information on halogen lamps for studio, stage and TV see the brochure:

[&]quot;Good news for show business"

[&]quot;Halogen High Voltage Lamps" cross reference list

| r |
|---|
| |
| |

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.