

64647 120 W 24 V

Low-voltage halogen lamps without reflector

Areas of application

- Lamps for special luminaires
- Medical fiber optics (HLX)



Product benefits

- Compared to standard lamps up to 10 % higher luminous efficacy (HLX)
- Instant light (HLX)

Product features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)
- HLX tungsten halogen low-voltage lamp with or without reflector
- Dimmable (HLX)



July 11, 2019, 12:43:23 64647 120 W 24 V

Technical data


Electrical data

Nominal voltage	24.0 V
Nominal wattage	120.00 W

Photometrical data

Nominal luminous flux	3600 lm

Dimensions & weight





0 0

Diameter	13.0 mm
Length	44.0 mm
Light center length (LCL)	30.0 mm
Filament length	2.30 mm
Illuminated field	2.3*6.4 mm ²
Filament diameter	6.4 mm

Lifespan

Additional product data

Base (standard designation)	G6.35
Minimum diameter of lamp enclosure	14 mm

Capabilities

Dimmable	Yes
Burning position	Any

Certificates & standards

Country specific categorizations

64647 120W 24V

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321107114	OSRH64647	-	-	-
4008321107114	OSRH64647	-	-	-



Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321107114	64647 120 W 24 V	Folding carton box 1	25 mm x 23 mm x 70 mm	0.04 dm³	5.00 g
4008321107121	64647 120 W 24 V	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm³	241.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.