

# Mod. 1913 B

COPOLYMER POLYPROPYLENE WATERPROOF CASE





METRIC MM-KG-C°

INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH W WIDTH D DEPTH LID BASE	190 mm 125 mm 135 mm 20 mm 115 mm	L LENGTH W WIDTH D DEPTH	216 mm 180 mm 152 mm	WEIGHT EMPTY WEIGHT WITH FOAM WEIGHT WITH CUSTOM FOAM VOLUME BUOYANCY OPERATING TEMPERATURE	0.85 Kg 0.92 Kg Kg 3.20 lt 2.40 Kg/max °C min -33 / max +90

IMPERIAL IN-LBS-F°

W

INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH W WIDTH D DEPTH LID BASE	7 1/2 in 4 15/16 in 5 5/16 in 13/16 in 4 1/2 in	L LENGTH W WIDTH D DEPTH	8 1/2 in 7 1/16 in 6 in	WEIGHT EMPTY WEIGHT WITH FOAM WEIGHT WITH CUSTOM FOAM VOLUME BUOYANCY OPERATING TEMPERATURE	1.87 lbs 2.02 lbs lbs 0.79 gal 5.29 lbs/max °F min -27.4 / max +194
-	L LENGTH W WIDTH D DEPTH LID	L LENGTH 7 1/2 in W WIDTH 4 15/16 in D DEPTH 5 5/16 in LID 13/16 in	L LENGTH 7 1/2 in L LENGTH W WIDTH 4 15/16 in W WIDTH D DEPTH 5 5/16 in D DEPTH LID 13/16 in	L LENGTH 7 1/2 in L LENGTH 8 1/2 in W WIDTH 4 15/16 in W WIDTH 7 1/16 in D DEPTH 5 5/16 in D DEPTH 6 in LID 13/16 in	L LENGTH 7 1/2 in L LENGTH 8 1/2 in WEIGHT EMPTY W WIDTH 4 15/16 in W WIDTH 7 1/16 in WEIGHT WITH FOAM D DEPTH 5 5/16 in D DEPTH 6 in WEIGHT WITH CUSTOM LID 13/16 in BASE 4 1/2 in BUOYANCY OPERATING



# **FEATURES**



### CORROSION PROOF METAL HINGES WITH LID STAY FEATURES







**OPTIONAL SHOULDER STRAP (universal)** (art. SHOULDERKIT.U)



#### LATCH





#### **INTERNAL SLOTS**

Internal slots for optional panel mounting brackets or panel mounting rings



#### PVC WATERPROOF I. D. REMOVABLE LABEL

(Art. LABELCOVER + nr. art.)

#### MANUAL PRESSURE RELEASE VALVE

The internal stop ring prevents valve from being completely extracted (Art. PURGEVALVE.B)



# ACCESSORIES

#### PROTECTIVE SLEEVE FOR PC 13'-13.3'""

TOP ENVELOPE 13

Protective padded notebook sleeve. Protects the laptop from shocks and scratches.



#### PADDED DIVIDER FOR 1913 DIV1913

Padded dividers with internal adjustable partitions. Ideal to protect and transport any kind of sensitive equipment. Thanks to their modularity, they can be easily combined.

## CONVOLUTED FOAM SET FOR CASE 1908 AND 1913

LIDFOAM.19

(includes 2 pcs.)





## ADJUSTABLE SHOULDER KIT

SHOULDERKIT.U

The kit is composed by: shoulder strap with plastic endings, 4 threaded knots, 2 metal plates. (min. extension 106 cm, max. extension 201 cm). The strap comes with the Explorer logo. Suitable for models: 1908, 1913, 2209, 2214, 3005, 4412, 4419, 5117, 9413, 11413 and 13513.





#### PATENTED HEAVY DUTY BRASS PADLOCK WITH KEYS

EXPL PADLOCK

Designed to fit snug to the Explorer case mould so as not to swing out



### PATENTED COMBINATION PADLOCK

EXPL COMBILOCK

Designed to fit snug to the Explorer case mould so as not to swing out

# BLIND INSERT

KIT.EXPL.PLUGS

Kit includes 6 pcs.

Whenever the slots are not going to be used for in-built applications, those can be closed by blind inserts that will give the case a better and finished interior look.



#### TSA APPROVED PADLOCK WITH COMBINATION

EXPL TSA.DIGILOCK

The new TSA approved padlocks allow tsa® airport security agents to open the case withoutdestrying the lock. TSA agents are trained to recognize the travel sentry certified logo and should not break the case lock.





#### METAL BRACKET

KIT SUPP.EXPL.

#### Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly

# FOAM SET FOR CASE 1913 FOAM.1913 Layers of pre cubed foam for the bottom and convoluted foam for the lid



#### PLASTIC BRACKET

KIT SUPP.PLAST.

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly



# **SPARE PARTS**



# Polyurethane o-ring seal for models 1908 and 1913

Includes: 1 o-ring



#### Manual pressure release valve for models from 1908 to 2214 KIN.0525

- Includes: 1 black purge valve (+ o-ring + pin) 1 threaded bush
- 1 snap ring (Seeger)



#### Latch for models from 1908 to 2214 KIN.0442

- Includes: 1 black latch
- 1 fixing pin



#### Name tag holder for models 1908, 1913, 2209 and 2214 KIN.0497

Includes: 1 transparent name tag holder





#### Handle for model from 1908 to 2214

KIN.0478 Includes: 1 black handle 2 fixing pins



#### EPDM extruded o-ring seal for models 1908 and 1913

KIN.0430

Includes: 1 o-ring