

## 64380

Halogen lamps, current-controlled, double-ended




### Product benefits

- Reduced operation and maintenance costs due to long lifetime
- Instant and constant light output over the lamp life
- Flicker-free operation
- Mercury-free

### Product features

- Dimmable
- Infrared radiation output that provides light in the worst of conditions



## Product datasheet

### Technical data


#### Electrical data

Lamp current	6.6 A
Nominal wattage	200.00 W

#### Photometrical data

Nominal luminous flux	4400 lm
Luminous intensity	28000 cd

#### Dimensions & weight



Diameter	15.0 mm
Length	65.6 mm
Length with base excl. base pins/connection	65.00 mm

#### Lifespan

Lifespan	1000 h
----------	--------

#### Additional product data

Base (standard designation)	R7s
-----------------------------	-----

#### Capabilities

Dimmable	Yes
Burning position	p15

#### Country specific categorizations

LIF	J1/40
Order reference	200W R7S-18 25X

Product datasheet

Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4050300209944	OSRH64380	-	4739726	-

## Product datasheet

---

### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
0046135587078	64380	Folding carton box 1	- x - x -		
4008321282415	64380	Shipping carton box 25	170 mm x 170 mm x 115 mm	3.32 dm <sup>3</sup>	503.00 g
4050300209944	64380	Folding carton box 1	113 mm x 33 mm x 33 mm	0.12 dm <sup>3</sup>	17.33 g
4050300209951	64380	Shipping carton box 25	180 mm x 130 mm x 180 mm	4.21 dm <sup>3</sup>	565.33 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### References / Links

For more information on airfield lamps see the brochure:

"The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.